



Waterborne, interior latex acrylic paint intended for painting of walls and ceiling which provides durable, flat finish. Flat.



BENEFITS & GENERAL DESCRIPTION:

Waterborne, latex acrylic paint intended for decorative and protective painting of walls and ceilings as well as additional elements like cornices, rosettes, etc.

SUPER HIDE® ZERO VOC INTERIOR FLAT 355 creates flat finish and characterizes durability, quick drying time and very good application parameters.

Product is users safe and environmental friendly in trace VOC* content formula.

Paint is recommended for residential objects like apartments and houses, commercial (e.g. offices) and public health care objects, public utility facilities, schools as well as food care objects.

Product meets the LEED® v4 Credit requirements.

The paint is available in bases intended to tint and ready-made, attractive color "Ceiling White 04".

PROPERTIES:

- *ecological formula with trace VOC* content*
- *very high hiding power, easy application and spatter-resistant*
- *excellent adhesion to the substrate*
- *meets LEED® v4 Credit requirements*

Technical information – White (01)	
vehicle type:	acrylic dispersion
pigment type **:	titanium dioxide
volume solids**:	29 ± 2%
coverage:	approx. 10-12 m ² /l for one coat depending on surface texture, porosity and absorbing properties, application method and painting tool used. Test should be performed in order to determine the coverage of the given surface.
recommended film thickness:	
- wet	96,52 µm
- dry	27,94 µm
dry time (at temp. + 25°C and relative air humidity 50%):	
- to touch:	min. 1 hours
- to recoat (the next coat application):	min. 3 hours
- full cure and final technical parameters and durability:	min. 14 days
dries by:	evaporation and coalescence
viscosity **:	98 ± 3 KU
flash point:	none
gloss/sheen:	flat (0-2 @ 85°)
colors:	Bases 1X, 2X, 3X intended for tinting in the GENNEX® Platform system. Wide range of Benjamin Moore colors. Version "Ceiling White 04" available in ready-made color.
reaction to fire:	Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84.
painted surface temperature:	min +10°C, max. +32°C
thin with:	not recommended, if needed use clean water
clean up thinner:	clean water
weight per 1 l **:	1,43 kg
storage temperature:	min. +5°C, max. +32°C
VOC:	* Product with trace VOC content according to "The European Council of the Paint, Printing Ink, and Artist's Colours Industry" (CEPE) and "British Coating Federation" guidelines. EU VOC limit for this product (Cat. A/a): 30 g/l (2010). Max. VOC: < 0.76 g/l.
Natural environment protection/ecology:	Product qualifies for: LEED® v4 Credit, CDPH v1 Emission Certified, CHPS low emitting credit (Collaborative for High Performance Schools)
COMPLIANCE & CERTIFICATIONS:	Master Painters Institute MPI #53, 53 X-Green™, 143.
packaging***:	3,78 l; 18,9 l

** reported values are for Pastel Base 1X and can be different in case of other Bases.

***3,78 L = 1 gallon

RECOMMENDED FOR

Range of use: traditional cement-lime and cement plasters, thin-layered mineral and acrylic plasters, gypsum filling materials, gypsum substrates, dry walls, wallpapers, construction building blocks, concrete, latex paint coats renovation.

Surface preparation:

- *new (not painted before) surfaces:*

New cement-lime and cement plasters and concrete must be allowed to cure at least 4 weeks. Surfaces finished with gypsum fillers or plasters can be decorated after their full drying and curing. Remove dirt, dust, wax, grease and oil

spots and loose or weak parts of substrate. All imperfections and cracks must be filled with a special patching compound, similar to original used one. Remove microorganisms (e.g. fungus and mildew) using a special agent. Prime the substrate according to below recommendations:

Walls and ceiling prime with one from the following products: *SUPER HIDE® ZERO VOC INTERIOR LATEX PRIMER 354* or *FRESH START® HIGH-HIDING ALL PURPOSE PRIMER 046*.

In case of weak substrate in order to its reinforcement, before one of mentioned primer application use a primer *COROTECH® CLEAR ACRYLIC SEALER V027* or *ULTRA SPEC® MASONRY INTERIOR/EXTERIOR 100% ACRYLIC SEALER 608 00 CLEAR*.

On some difficult substrates with some spots and stains use a special priming paint *FRESH START® HIGH-HIDING ALL PURPOSE PRIMER 046*.

Warning: the priming is a technological requirement in case of not primed or not painted substrates.

● **previously painted surfaces:**

Remove dirt, dust, wax, grease and oil spots, all paint layers and loose or weak parts of the substrate. The glossy surfaces must be dulled. All imperfections and cracks must be filled with a special patching compound, similar to original used one. Remove microorganisms (e.g. fungus and mildew) using a special agent.

In case of old paint layers renovation the test should be performed on small surface area. Positive result, decides on application of the product on the whole surface.

The priming is not necessary if existing coat is in an excellent condition. Exposed parts of substrate also those after the reparation must be primed with a proper primer from Benjamin Moore & Co. offer.

Walls and ceiling prime with one from the following products: *SUPER HIDE® ZERO VOC INTERIOR LATEX PRIMER 354* or *FRESH START® HIGH-HIDING ALL PURPOSE PRIMER 046*.

● **wallpapered surfaces:** remove all wallpapers with a weak adherence to the substrate, remove old adhesive, sand, remove dust and glue using the proper adhesive. Remove dirt, dust, wax, grease and oil spots from wallpapers and prime with *SUPER HIDE® ZERO VOC INTERIOR LATEX PRIMER 354* or *FRESH START® HIGH-HIDING ALL PURPOSE PRIMER 046*.

Warning: use a primer in the color similar to the top coat (if there is a technical possibilities; see the details in TDSs of selected primer).

APPLICATION

The substrate must be solid, completely dry, clean and free of dust. The paint is in ready to use form. Stir thoroughly before and during use. Apply min. two coats after min. 4 hours from priming with *SUPER HIDE® ZERO VOC INTERIOR LATEX PRIMER 354*, min. 12 hours in case of *COROTECH® CLEAR ACRYLIC SEALER V027* or *ULTRA SPEC® MASONRY INTERIOR/EXTERIOR 100% ACRYLIC SEALER 608 00 CLEAR*, min. 24 hours in case of use *FRESH START® HIGH-HIDING ALL PURPOSE PRIMER 046*.

Apply with brush, roller or spraying gun. For airless method provide the following parameters: pressure 124÷206 bar and tip 0.015-0.017. Work using „wet in wet” system (that is, continuously, not allowing the paint to dry out when painting with a roller), avoiding creating overlaps. Technological breaks must be planned at the wall corners or other elements.

When painting job is conducted in high temperature, the relative air humidity below 45%, in direct sunlight or windy conditions add *518 EXTENDER* to paint in the amount of max. 235 ml to 3,78 l paint. It's possible also to add some clean water in the same amount. Never add other paints or solvents.

The next coat apply after min. 3 hours.

Do not apply on the substrates painted previously with limewash or glue paints.

It is recommended to use BENJAMIN MOORE or PREMIER painting tools and FrogTape® (with PaintBlock Technology®), KIP® or Painter's Matte Green® masking tapes.

Weather conditions during and after application:

Carry out the painting work at the air and substrate temperature > +10°C. The optimal conditions: + 20°C and relative air humidity 50%.

Drying time:

At the temperature of +25°C and relative air humidity 50% the paint dries approx. 1 hour.

At mentioned weather conditions the next coat apply after min. 3 hours.

Clean up: wash painting tools in warm soapy water immediately after use.

Warning: Use system: paint *SUPER HIDE® ZERO VOC INTERIOR FLAT 355* and primers from Benjamin Moore & Co. offer. Ensure enough amount of paint from one production batch in order to avoid some color differences.

Do not use Bases 1X, 2X, 3X not tinted in GENNEX® Platform system.

Only GENNEX® Waterborne Colorants can be added to *SUPER HIDE® ZERO*® paint.

The coat achieves the final parameters after min. 14 days after application. Do not wash/clean – washing will cause the partially gloss grade rise in the washed places.

Producer is not responsible for bad quality of the painted surface if the above instructions aren't obeyed. Producer is not responsible for the damages appeared in results of use over 3,78 l of paint, because to this quantity any defects of product should be demonstrated and notified in the proper point of sale.

ENVIRONMENTAL, HEALTH & SAFETY INFORMATION:



MSDS available on demand of consumer.

WARNING

Contains 2-Methyl-4-isothiazolin-3-one.

Hazard statements

H317 - May cause an allergic skin reaction.

EUH208 - Contains (1,2-Benzisothiazolin-3-one, 5-Chloro-2-methyl-3(2H)-isothiazolone mixture with 2-methyl-3(2H)-isothiazolone (3:1). May produce an allergic reaction

EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 - Wear protective gloves.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P321 - Protect against consumption. If swallowed, seek medical advice immediately - show the packaging or label.

P501 - Do not pour liquid residues into sewerage systems. They should be referred to specialized companies with appropriate authorization for disposal. Empty cans and liquid waste should be recycled or disposed of in accordance with local regulations.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

EXPIRE DATE: 4 years from the production date in the factory-sealed package The expire date is indicated on the packaging.

CERTIFICATES: the product is qualified with Hygienic Certificate.



This specification is effective from: 09.2023.

B.M. Polska Sp. z o. o. guarantee the higher product quality, however can not control the way of its application. The producer is not responsible for the work of Designer and Contractor. The information presented in this technical data sheet were given in good faith, in accordance with the current state of knowledge and practical experience. It does not relieve you of responsibility for carrying out work in accordance with the building construction rules as well as health and safety regulations.

B. M. Poland Sp. z o. o. is not liable for any damage and defects caused by the combined use of the offered products with materials from the portfolio of other manufacturers, as well as in the event of any recipe changes by buyers and users.

B.M Polska Sp. z o. o. reserves the right to change the content in subsequent editions of the technical data sheet without prior notification of the fact to the Clients and full right to modify the products as part of their technological development.

PRODUCER: Benjamin Moore & Co., 101 Paragon Drive, Montvale, NJ 07645, USA, tel. (201) 573 9600, www.benjaminmoore.com
EXCLUSIVE REPRESENTATIVE: B.M. Polska Sp. z o.o., ul. Polczyńska 100, 01-302 Warszawa, tel. + 48 22 533 52 90, fax. +48 22 533 52 99 www.benjaminmoore.pl www.bmpolska.com